

## Keenetic KN-2212 router wireless Fast Ethernet Banda singola (2.4 GHz) 4G Grigio, Bianco

**Marchio :** Keenetic

**Codice prodotto:** KN-2212-01-EU

**Nome del prodotto :** KN-2212

ASR1803S LTE modem, MT7628N 575 MHz, 128 MB DDR2, 32 MB, 4 dBi, 159 mm x 110 mm x 29 mm, 236 g

Keenetic KN-2212. Tipo di connessione WAN: RJ-45. Banda Wi-Fi: Banda singola (2.4 GHz), Wi-Fi standard: Wi-Fi 4 (802.11n), Intervallo di trasferimento dei dati WLAN (max): 300 Mbit/s. Tipo di interfaccia LAN Ethernet: Fast Ethernet, Velocità trasferimento Ethernet LAN: 100 Mbit/s, Tecnologia di cablaggio: 10/100Base-T(X). Generazione di reti mobili: 4G, Standard 3G: HSDPA, HSPA+, HSUPA, WCDMA, Standard 4G: LTE-TDD & LTE-FDD. Algoritmi di sicurezza supportati: HTTPS, IPSec, WEP, WPA-PSK, WPA-PSK2, WPA2-Enterprise, WPA3-Enterprise



| WAN connection                  |                                                    | Security                          |                                 |
|---------------------------------|----------------------------------------------------|-----------------------------------|---------------------------------|
| Ethernet WAN *                  | ✓                                                  | Network address translation (NAT) | ✓                               |
| DSL WAN *                       | ✗                                                  | Protocols                         |                                 |
| SIM card slot *                 | ✓                                                  | DHCP client                       | ✓                               |
| 3G/4G USB modem compatibility * | ✓                                                  | DHCP server                       | ✓                               |
| WAN connection type             | RJ-45                                              | Universal Plug and Play (UPnP)    | ✓                               |
| Wireless LAN features           |                                                    | Supported network protocols       | IPoE, PPPoE, PPTP, L2TP, 802.1x |
| Wi-Fi band *                    | Single-band (2.4 GHz)                              | Design                            |                                 |
| Top Wi-Fi standard *            | Wi-Fi 4 (802.11n)                                  | Product colour                    | Grey, White                     |
| WLAN data transfer rate (max) * | 300 Mbit/s                                         | Product type *                    | Tabletop router                 |
| Wi-Fi standards                 | Wi-Fi 4 (802.11n)                                  | Packaging content                 |                                 |
| Network                         |                                                    | Cables included                   | LAN (RJ-45)                     |
| Ethernet LAN *                  | ✓                                                  | AC adapter included               | ✓                               |
| Ethernet LAN interface type *   | Fast Ethernet                                      | Quick start guide                 | ✓                               |
| Ethernet LAN data rates         | 100 Mbit/s                                         | Antenna                           |                                 |
| Cabling technology              | 10/100Base-T(X)                                    | Antenna design *                  | External                        |
| Networking standards            | IEEE 802.11k, IEEE 802.11r, IEEE 802.11v           | Antenna gain level (max)          | 4 dBi                           |
| Policy-based routing            | ✓                                                  | Antennas quantity                 | 4                               |
| SSID-based VLAN assignment      | ✓                                                  | Detachable antenna(s)             | ✓                               |
| VPN support                     | OpenVPN (client/server), IPsec VPN (client/server) | Features                          |                                 |
| Mobile network                  |                                                    | Built-in processor                | ✓                               |
| Mobile network generation       | 4G                                                 | Processor manufacturer            | MediaTek                        |
| 3G standards                    | HSDPA, HSPA+, HSUPA, WCDMA                         | Processor model                   | MediaTek MT7628N                |
| 4G standard                     | LTE-TDD & LTE-FDD                                  | Processor frequency               | 575 MHz                         |
| SIM card type                   | NanoSIM                                            | Internal memory                   | 128 MB                          |
| Ports & interfaces              |                                                    | Internal memory type              | DDR2                            |
| Ethernet LAN (RJ-45) ports *    | 4                                                  | Flash memory                      | 32 MB                           |

| Ports & interfaces               |                                                                        | Power                              |              |
|----------------------------------|------------------------------------------------------------------------|------------------------------------|--------------|
| USB port *                       | ✗                                                                      | Power source type *                | AC           |
| Management features              |                                                                        | AC input voltage                   | 100 - 240 V  |
| Wi-Fi Multimedia (WMM)/(WME)     | ✓                                                                      | AC input frequency                 | 50/60 Hz     |
| Bandwidth control                | ✓                                                                      | Output voltage                     | 12 V         |
| Quality of Service (QoS) support | ✓                                                                      | Output current                     | 1 A          |
| WPS push button                  | ✓                                                                      | Operational conditions             |              |
| Security                         |                                                                        | Operating temperature (T-T)        | 0 - 40 °C    |
| Security algorithms              | HTTPS, IPSec, WEP, WPA-PSK, WPA-PSK2, WPA2-Enterprise, WPA3-Enterprise | Operating relative humidity (H-H)  | 20 - 95%     |
| Guest access                     | ✓                                                                      | System requirements                |              |
| Stateful Packet Inspection (SPI) | ✓                                                                      | Mobile operating systems supported | Android, iOS |
| DoS attack prevention            | ✓                                                                      | Weight & dimensions                |              |
| Parental control                 | ✓                                                                      | Width                              | 159 mm       |
| MAC address filtering            | ✓                                                                      | Depth                              | 110 mm       |
| System event log                 | ✓                                                                      | Height                             | 29 mm        |
|                                  |                                                                        | Weight                             | 236 g        |
|                                  |                                                                        | Packaging data                     |              |
|                                  |                                                                        | Number of products included        | 1 pc(s)      |



4897082922131

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.

Publication date: 08-APR-2025. Prints or copies of Information are only valid on the printed Publication date