

## Keenetic KN-4910 router wireless Fast Ethernet Dual-band (2.4 GHz/5 GHz) 4G Grigio, Bianco

**Marchio :** Keenetic

**Codice prodotto:** KN-4910-01-EU

**Nome del prodotto :** KN-4910

AC1200 , MT7628N 575 MHz, 128 MB DDR2, 32 MB, 4 x 100 Mbps, 159 mm x 110 mm x 29 mm, 236 g  
Keenetic KN-4910. Tipo di connessione WAN: RJ-45. Banda Wi-Fi: Dual-band (2.4 GHz/5 GHz), Wi-Fi standard: Wi-Fi 5 (802.11ac), Intervallo di trasferimento dei dati WLAN (max): 867 Mbit/s. Tipo di interfaccia LAN Ethernet: Fast Ethernet, Velocità trasferimento Ethernet LAN: 10,100 Mbit/s, Tecnologia di cablaggio: 10/100Base-T(X). Generazione di reti mobili: 4G, Standard 3G: HSDPA, HSPA+, HSUPA, WCDMA, Standard 4G: LTE-TDD & LTE-FDD. Algoritmi di sicurezza supportati: OWE, WEP, WPA-PSK, WPA-PSK2, WPA2-Enterprise, WPA2-PSK, WPA3-Enterprise, WPA3-PSK



| WAN connection                  |                                                    | Security                          |                                 |
|---------------------------------|----------------------------------------------------|-----------------------------------|---------------------------------|
| Ethernet WAN *                  | ✓                                                  | DoS attack prevention             | ✓                               |
| DSL WAN *                       | ✗                                                  | Parental control                  | ✓                               |
| SIM card slot *                 | ✓                                                  | MAC address filtering             | ✓                               |
| 3G/4G USB modem compatibility * | ✗                                                  | Network address translation (NAT) | ✓                               |
| WAN connection type             | RJ-45                                              | Protocols                         |                                 |
| Wireless LAN features           |                                                    | DHCP client                       | ✓                               |
| Wi-Fi band *                    | Dual-band (2.4 GHz / 5 GHz)                        | DHCP server                       | ✓                               |
| Top Wi-Fi standard *            | Wi-Fi 5 (802.11ac)                                 | Universal Plug and Play (UPnP)    | ✓                               |
| WLAN data transfer rate (max) * | 867 Mbit/s                                         | Switching protocols               | IPoE, PPPoE, PPTP, L2TP, 802.1x |
| Wi-Fi standards                 | Wi-Fi 4 (802.11n), Wi-Fi 5 (802.11ac)              | Design                            |                                 |
| Network                         |                                                    | Product colour                    | Grey, White                     |
| Ethernet LAN *                  | ✓                                                  | Product type *                    | Tabletop router                 |
| Ethernet LAN interface type *   | Fast Ethernet                                      | Antenna                           |                                 |
| Ethernet LAN data rates         | 10,100 Mbit/s                                      | Antenna design *                  | External                        |
| Cabling technology              | 10/100Base-T(X)                                    | Antenna gain level (max)          | 4 dBi                           |
| Networking standards            | IEEE 802.11k, IEEE 802.11r, IEEE 802.11v           | Antennas quantity                 | 4                               |
| Port forwarding                 | ✓                                                  | Features                          |                                 |
| Port triggering                 | ✓                                                  | Built-in processor                | ✓                               |
| Policy-based routing            | ✓                                                  | Processor manufacturer            | MediaTek                        |
| SSID-based VLAN assignment      | ✓                                                  | Processor model                   | MediaTek MT7628N                |
| VPN support                     | OpenVPN (client/server), IPsec VPN (client/server) | Processor frequency               | 575 MHz                         |
| Mobile network                  |                                                    | Internal memory                   | 128 MB                          |
| Mobile network generation       | 4G                                                 | Internal memory type              | DDR2                            |
| 3G standards                    | HSDPA, HSPA+, HSUPA, WCDMA                         | Flash memory                      | 32 MB                           |
| 4G standard                     | LTE-TDD & LTE-FDD                                  | Power                             |                                 |
|                                 |                                                    | Power source type *               | AC                              |
|                                 |                                                    | AC input voltage                  | 100 -240 V                      |

| Mobile network                   |                                                                                   | Power                              |           |
|----------------------------------|-----------------------------------------------------------------------------------|------------------------------------|-----------|
| 4G bands supported               | 800,850,900,1800,2100,2300,2500,2600 MHz                                          | AC input frequency                 | 50/60 Hz  |
| SIM card type                    | NanoSIM                                                                           | Output voltage                     | 12 V      |
| Ports & interfaces               |                                                                                   | Output current                     | 1 A       |
| Ethernet LAN (RJ-45) ports *     | 4                                                                                 | Operational conditions             |           |
| USB port *                       | ✗                                                                                 | Operating temperature (T-T)        | 0 - 40 °C |
| Management features              |                                                                                   | Operating relative humidity (H-H)  | 20 - 95%  |
| Wi-Fi Multimedia (WMM)/(WME)     | ✓                                                                                 | System requirements                |           |
| Bandwidth control                | ✓                                                                                 | Mobile operating systems supported |           |
| Quality of Service (QoS) support | ✓                                                                                 | Android, iOS                       |           |
| MU-MIMO technology               | ✓                                                                                 | Weight & dimensions                |           |
| MIMO                             | ✓                                                                                 | Width                              | 159 mm    |
| Security                         |                                                                                   | Depth                              | 110 mm    |
| Security algorithms              | OWE, WEP, WPA-PSK, WPA-PSK2, WPA2-Enterprise, WPA2-PSK, WPA3-Enterprise, WPA3-PSK | Height                             | 29 mm     |
| Guest access                     | ✓                                                                                 | Weight                             | 236 g     |
| Stateful Packet Inspection (SPI) | ✓                                                                                 | Packaging data                     |           |
| Schedule access                  | ✓                                                                                 | Number of products included        | 1 pc(s)   |



4897082922155

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.

Publication date: 08-APR-2025. Prints or copies of Information are only valid on the printed Publication date