TP-Link TC40GW telecamera di sorveglianza Torretta Telecamera di sicurezza IP Esterno 1920 x 1080 Pixel Soffitto/Parete/Palo

Marchio : TP-Link

Codice prodotto: TC40GW

**Nome del prodotto :** TC40GW

TP-Link TC40GW. Tipo: Telecamera di sicurezza IP, Posizionamento supportato: Esterno, Tecnologia di connessione: Cablato. Tipo di montaggio: Soffitto/Parete/Palo, Colore del prodotto: Bianco, Fattore di forma: Torretta. Angolo di visione dell'obiettivo, orizzontale: 105°, Angolo di visione dell'obiettivo, verticale: 59°, Angolo di visione dell'obiettivo, diagonale: 122°. Tipo sensore: CMOS, Dimensioni sensore ottico: 25,4 / 2,9 mm (1 / 2.9"). Distanza di visione notturna: 29.9 m, Lunghezza d'onda a infrarossi: 850 nm

Performance

Type *	IP security camera
Placement supported *	Outdoor
Connectivity technology *	Wired
Antenna type	External
Antennas quantity	1

Design

Form factor *	Turret
Mounting type *	Ceiling/Wall/Pole
Product colour *	White
International Protection (IP) code	IP66

Camera

Lens viewing angle, horizontal	105°
Lens viewing angle, vertical	59°
Lens viewing angle, diagonal	122°
Tilt angle range	60 - 130°
Pan range	340 - 360°

Image sensor

Optical sensor size	25.4 / 2.9 mm (1 / 2.9")
Sensor type *	CMOS

Lens system

Maximum aperture number	1.65

Storage

Card reader integrated	✔
Compatible memory cards	MicroSD (TransFlash)
Maximum memory card size	512 GB

Ports & interfaces

Ethernet LAN (RJ-45) ports	1

Security

Built-in siren	✔
Siren noise level	99 dB
Alert notification type	Snapshot alert message
Motion sensor	✔
Human and vehicle targets classification	✔

Management features

Cloud-managed *	✔
Reset button	✔

Power

Power source type *	DC, PoE
AC input voltage	100 - 240 V
AC input frequency	50/60 Hz
Power consumption (typical)	2.8 W
Power consumption (max)	9.5 W
DC output voltage	12

Night vision

Night vision *	✔
Night vision distance	29.9 m
Infra-red wavelength	850 nm

Video

Maximum resolution *	1920 x 1080 pixels
Video formats supported	H.264
Frame rate	30 fps

Audio

Built-in speaker(s)	✔
Audio system	2-way
Built-in microphone	✔

Network

Ethernet LAN *	✔
Networking standards	IEEE 802.3af, IEEE 802.3at
Supported network protocols	Protocol TCP/IP, DHCP, ICMP, DNS, NTP, HTTPS, TCP, UDP
SIM card slot	✔
SIM card type	NanoSIM
Mobile network connection	✔
Mobile network generation	4G
4G standard	LTE-TDD & LTE-FDD

Power

DC output current	1 A

Operational conditions

Operating temperature (T-T)	-30 - 60 °C
Storage temperature (T-T)	-40 - 60 °C
Operating relative humidity (H-H)	10 - 90%
Storage relative humidity (H-H)	0 - 90%

System requirements

Mobile operating systems supported	Android, iOS

Weight & dimensions

Width	106 mm
Depth	140 mm
Height	234 mm
Weight	430 g
Cable length	3 m

Sustainability

Compliance certificates	BSMI, CE, NCC, RCM, RoHS, VCCI

Packaging content

Number of cameras *	1
Mounting brackets included	✔
Anchors included	✔
Quick start guide	✔

8885020628548